


CIVE 3205

Example BC05b

Calculate points on Interaction Curve

Rectangular X-section



1) stress distribution 1)

$$C = C_y = 100 \text{ mm} \times 300 \text{ mm} \times 345 \frac{\text{N}}{\text{mm}^2} \times 10^{-3} \frac{\text{kN}}{\text{N}}$$

$$C_y = 10350 \text{ kN}$$

$$T = 0$$

$$M = 0$$

2) stress distribution 2)

$$C = 0$$

$$T = 100 \text{ mm} \times 150 \text{ mm} \times \frac{345 \text{ N}}{\text{mm}^2} \times 10^{-3} \frac{\text{kN}}{\text{mm}}$$

$$T = 5175 \text{ kN}$$

$$M = M_p = T \left(\frac{d}{2} \right)$$

$$= 5175 \text{ kN} \times \frac{300 \text{ mm}}{2} \times 10^{-3} \frac{\text{m}}{\text{mm}}$$

$$M_p = 776.25 \text{ kN-m}$$

3/5

3) stress distribution 3)

for $y_0 = 60$

$$C = 2 \times 60 \times 100 \text{ mm}^2 \times 345 \frac{\text{N}}{\text{mm}^2} \times 10^{-3} \frac{\text{kN}}{\text{N}}$$

$$C = 4140 \text{ kN}$$

$$T = (150 - 60) \text{ mm} \times 100 \text{ mm} \times 345 \frac{\text{N}}{\text{mm}^2} \times 10^{-3} \frac{\text{kN}}{\text{N}}$$

$$= 3105 \text{ kN}$$

$$M = T \left(d - \frac{y_0}{2} \times z \right)$$

$$= 3105 \text{ kN} \times (300 \text{ mm} - 90 \text{ mm}) \times 10^{-3} \frac{\text{m}}{\text{mm}}$$

$$M = 652.05 \text{ kN-m}$$

1) $y_0 = 150$

$$C = C_y$$

$$c/c_y = 1$$

$$M = 0$$

$$M/M_p = 0$$

2) $y_0 = 0$

$$C = 0$$

$$c/c_y = 0$$

$$M = M_p$$

$$M/M_p = 1$$

3) $y_0 = 60 \text{ mm}$


$$C = 4140 \text{ kN}$$

$$c/c_y = \frac{4140}{70350} = 0.4$$

$$M = 652.05$$



$$M/M_p = \frac{652.05}{776.25} = 0.84$$

3 pts on I.C.



2) I-Shape (W250x73)

4/5



T_1 = tension in web

$$= (112.3 - 56.15) \times 8.6 \times 345 \times 10^{-3}$$

$$= 166.597 \text{ kN}$$

T_2 = tension in flange

$$= 254 \times 14.2 \times 345 \times 10^{-3}$$

$$= 1244.346 \text{ kN}$$


$$M = T_1 \left(56.15 + \frac{112.3 - 56.15}{2} \right) \times 2$$

$$+ T_2 \left(253 - 2 \times \frac{14.2}{2} \right) \times 10^{-3}$$

$$\underline{\underline{M = 325.21 \text{ kN-m}}}$$

2) N.A in flange $y_0 = 119.4 \text{ mm}$

5/5



$$\begin{aligned}C_1 &= \text{compression in web} \\&= 224.6 \times 8.6 \times 345 \times 10^{-3} \\&= 666.388 \text{ kN}\end{aligned}$$

$$\begin{aligned}C_2 &= \text{compression in part of one flange} \\&= 254(119.4 - 112.3) \times 345 \times 10^{-3} \\&= 622.173 \text{ kN}\end{aligned}$$

$$\begin{aligned}C &= C_1 + 2C_2 \\&= 666.388 + 2 \times 622.173\end{aligned}$$

$$C = \underline{\underline{1910.7 \text{ kN}}}$$

T = tension in part of flange

$$t' = 126.5 - 119.4 = 7.1 \text{ mm}$$

$$\begin{aligned}T &= 7.1 \times 254 \times 345 \times 10^{-3} \\&= 622.173 \text{ kN}\end{aligned}$$

$$\begin{aligned}M &= T(d - 2\frac{t'}{2}) \\&= 622.173 \times (253 - 7.1) \times 10^{-3}\end{aligned}$$

$$\underline{\underline{M = 152.99 \text{ kN-m}}}$$